



Serving the Hospitality Industry with Advanced  
**IP and Analog** Telephony Solutions  
**Worldwide**

## AMT-6210-S

Two-Line  
Corded Analog  
Speakerphone



### Features

- Auto Line Select
- 3-way Conference
- Line in use Indicator
- 2-line Speakerphone
- Hearing Aid Compatible
- Unique Customizable Faceplate
- Message Waiting & Ring Indicator
- 10 Programmable Guest Service keys
- Adjustable Handset & Speakerphone Volume Control

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



PRODUCT OPTIONS



**AMT-6210**  
Two-Line Telephone  
10 Guest Service Keys  
No Speakerphone



**AMT-6205-S**  
Two-Line Telephone  
5 Guest Service Keys  
with Speakerphone



**AMT-6200-S**  
Two-Line Telephone  
No Guest Service Keys  
with Speakerphone

Custom Guest Service Key configuration available

SPECIFICATIONS

Product Spec	<ul style="list-style-type: none"> <li>• AMT-6210 Two-Line Non-Speakerphone</li> <li>• AMT-6210-S Two-Line Speakerphone</li> <li>• AMT-6200-S Two-Line Speakerphone w/o Guest Service Keys</li> <li>• Black Standard (Ash Optional)</li> <li>• Textured</li> <li>• Customizable Faceplate, 205mm x 80mm</li> <li>• Line Power, 24 to 56 Volts</li> <li>• Standard DTMF</li> <li>• 600ms and 300ms</li> <li>• Z</li> <li>• Hearing Aid Compatible</li> <li>• RJ11 Line, RJ11 Data and RJ9 Handset</li> <li>• 10' Line cord (15' upon request) &amp; 10' Coiled cord</li> <li>• 8.7" x 6.2" x 4.3"</li> <li>• 804g</li> </ul>	
Color		
Finish		
Faceplate		
Power		
Signaling		
Flash Timing		
Ring Equivalence		
Handset		
Jacks		
Cords		
Dimensions		
Weight		
Regulatory	USA	EUROPE
EMI	Part 15B, 15D	EN 3014089-1, 3014089-6, 301406
SAR		EN 50360, 50361
PTSN		TBR 21
RoHS	<ul style="list-style-type: none"> <li>• Comply with directive 2002/95/EC RoHS (2005/613/EC)</li> </ul>	
DECT		
Temperature	<ul style="list-style-type: none"> <li>• Storage</li> <li>Cold point at -10 C</li> <li>Hot point at +60 C</li> </ul>	<ul style="list-style-type: none"> <li>• Operating</li> <li>Cold point at 0 C</li> <li>Hot point at +45 C</li> </ul>

Serving the Hospitality Industry with **Advanced IP and Analog** Telephony Solutions Worldwide

