

AAX-Series

Wall-Mount
Corded Analog
Telephone



AAX-4100

Features

- Full Duplex Handset
- Magnetic Hookswitch
- Hearing Aid Compatible
- Handset Volume Control and Release key
- Message Waiting & Ring Indicator on Handset
- Customizable Hotel Logo and Dialing Instructions on Faceplate

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



PRODUCT



AAX-4100
Single Line Wall-Mount
Corded Telephone
No Guest Service Keys

SPECIFICATIONS

| | | | |
|---|--|--|--|
| <p>Product Spec</p> <p>Color</p> <p>Finish</p> <p>Faceplate</p> <p>Power</p> <p>Signaling</p> <p>Handset</p> <p>Jack</p> <p>Cords</p> <p>Dimensions</p> <p>Weight</p> | <ul style="list-style-type: none"> • AAX-4100 One-Line Wall-Mount with no Guest Service Keys • Black Standard (Ash Optional) • Textured • Full length customizable faceplate • Line Power, 24 to 56 Volts • Standard DTMF • Hearing Aid Compatible • RJ11 (Line) • 6" Line cord and 4' Coiled cord • 200mm (L) x 82mm (W) x 48mm (H) • 210g | | |
| <p>Regulatory</p> | <p>FCC</p> <ul style="list-style-type: none"> • Line Interface Signaling FCC Part 68 • EMI requirement FCC Part 15B <p>CE</p> <ul style="list-style-type: none"> • Line Interface Signal Requirement TBR21 • EMC requirement EN55022. EN55024 <p>RoHS</p> <ul style="list-style-type: none"> • Comply with directive 2002/95/EC RoHS (2005/613/EC) | | |
| <p>Temperature</p> | <table border="0"> <tr> <td> <ul style="list-style-type: none"> • Storage • Cold point at -10 C • Hot point at +60 C </td> <td> <ul style="list-style-type: none"> • Operating • Cold point at 0 C • Hot point at +45 C </td> </tr> </table> | <ul style="list-style-type: none"> • Storage • Cold point at -10 C • Hot point at +60 C | <ul style="list-style-type: none"> • Operating • Cold point at 0 C • Hot point at +45 C |
| <ul style="list-style-type: none"> • Storage • Cold point at -10 C • Hot point at +60 C | <ul style="list-style-type: none"> • Operating • Cold point at 0 C • Hot point at +45 C | | |